

Competitor comparison contactor lines low and middle power level

		Contactors low power				Contactors middle power level													
Pn	kW	2.2	3	4	5.5	4	5.5	7.5	11	15	18.5	22	30	37	45	55	75		
I _{motor} at 400V/1500 U _{min} ⁻¹	A	5	6.6	8.5	11.5	8.5	11.5	15.5	22	30	36	41	55	68	81	100	134		
I _{contactor} at AC-3/400V	A	6	7	9	12	9	12	17	25	32	40	50	65	80	95	115	150		
Moeller	DIL																		
	Contactor width mm	45				45, 45, 45, 60, 70, 100, 120													
SIEMENS	3RT10																		
	Contactor width mm	45				45, 55, 70, 120													
Schneider (Telemecanique)	LC1																		
	Contactor width mm	45				45, 45, 45, 75, 85, 120													
ABB																			
	Contactor width mm	45				44, 54, 54, 70, 90, 105													
Rockwell (Allen-Bradley)																			
	Contactor width mm	45				45, 45, 54, 72, 120													
GE	LS																		
	Contactor width mm	45				45, 55, 66, 75, 135													
xStart	DIL																		
	Contactor width mm	45				45, 55, 90													
xStart	DIL																		
	Contactor width mm	45																	